

BRADEN

BG8B-34039-01H

Features and Benefits

- API specification 2C-compliant personnel handling (available on some units)
- Cable wedge anchor system
- Cast iron ductile base
- Easy access to lubrication points
- Multiple gear ratio options to fit your application
- Sealed, high-efficiency planetary reduction gearing for continuous-duty performance
- Single or two-speed motors available
- Tension roller kit to help prevent spooling issues (available on some units)
- Underwind configuration available for clockwise hoisting



Line Pull	Unit Weight
9000lbs	307lbs
4082kg	139kg

Performance

	Imperial	Metric
Ratio	34.200:1	
Motor Displacement	3.920 ci	64.3 cc
Pressure	2721 psi	188.0 bar
Winch Flow	55 gpm	208.2 lpm
Rope Diameter	0.5000 in	12.8 mm
Cable Capacity	202 in	61 mm

Layer	Line Pull (lbs)	Line Speed (fpm)	Line Pull (kg)	Line Speed (mpm)
1	9000	202	4082	62
2	8100	225	3674	69
3	7360	248	3338	76
4	6750	270	3062	83
5	6230	293	2826	90
6	5790	315	2626	97

The last legal layer per ANSI is 5
D/d = 18:1

Applications for MODEL BG8

- Fishing/Marine
- Crane
- Utility
- Offshore

Resources:

- [Sales - LIT2077](#)
- [Sales - LIT2078](#)
- [Sales - LIT2309](#)
- [Service - LIT2204](#)
- [Service - LIT2492](#)

Material List - LIT2216

Material List - LIT2422

Material List - PB-108