

Gearmatic

GH30B-40090-04

Features and Benefits

- Equal speed forward and reverse operation
- High-efficiency, anti-friction bearings
- Spring-applied multi-disc brake



Line Pull	Unit Weight
23840lbs	0lbs
10813kg	0kg

Performance

	Imperial	Metric
Ratio	39.600:1	
Motor Displacement	9.020 ci	147.9 cc
Pressure	3003 psi	208.0 bar
Winch Flow	125 gpm	473.2 lpm
Rope Diameter	0.7500 in	19.1 mm
Cable Capacity	209 in	63 mm

Layer	Line Pull (lbs)	Line Speed (fpm)	Line Pull (kg)	Line Speed (mpm)
1	23840	209	10814	64
2	20920	238	9489	73
3	18640	267	8455	82
4	16800	296	7620	91
5	15300	326	6940	100
6	14040	355	6368	109
7	12970	384	5883	118
8	12060	413	5470	126
9	11260	442	5107	135

The last legal layer per ANSI is 9
D/d = 14:1

Applications for MODEL GH30

- Fishing/Marine
- Crane
- Oilfield
- Dredging
- Pipe Layer

Resources:

Sales - LIT2416

Sales - LIT2555

Service - LIT2363

Service - LIT2384

Service - LIT2397

Service - LIT2429

Service - PG-117

Material List - LIT2357

Material List - LIT2360

Material List - LIT2530

Material List - LIT2537