

Gearmatic

GH30B-40120-05

Features and Benefits

- Equal speed forward and reverse operation
- High-efficiency, anti-friction bearings
- Spring-applied multi-disc brake



Line Pull	Unit Weight
26840lbs	1400lbs
12174kg	635kg

Performance

	Imperial	Metric
Ratio	39.600:1	
Motor Displacement	12.030 ci	197.2 cc
Pressure	2439 psi	169.0 bar
Winch Flow	125 gpm	473.2 lpm
Rope Diameter	0.7500 in	19.1 mm
Cable Capacity	156 in	47 mm

Layer	Line Pull (lbs)	Line Speed (fpm)	Line Pull (kg)	Line Speed (mpm)
1	26840	156	12174	48
2	23550	178	10682	55
3	20980	200	9516	61
4	18920	222	8582	68
5	17220	244	7811	75
6	15810	266	7171	82
7	14610	288	6627	88
8	13570	310	6155	95
9	12680	332	5752	102

The last legal layer per ANSI is 9
D/d = 14:1

Applications for MODEL GH30

- Fishing/Marine
- Crane
- Oilfield
- Dredging
- Pipe Layer

Resources:

Sales - LIT2416

Sales - LIT2555

Service - LIT2363

Service - LIT2384

Service - LIT2397

Service - LIT2429

Service - PG-117

Material List - LIT2357

Material List - LIT2360

Material List - LIT2530

Material List - LIT2537